Product Datasheet

46mm ∅ Ultracapacitors

- Rated voltage 3VDC
- 600 and 1100F capacitance
- Long life with multimillion cycles
- Very high energy and power density
- Laser-weldable terminals
- Environmentally friendly product

ELECTRICAL SPECIFICATIONS		
Type	**C46W-3R0-0600**	**C46W-3R0-1100**
Rated Voltage V_R	3.00 V	3.00 V
Surge Voltage V_S[1]	3.10 V	3.10 V
Rated Capacitance C[2]	600 F	1100 F
Capacitance Tolerance[3]	0% / +30%	0% / +30%
DC ESR[2] (DC, 10 Hz)	<0.7 mΩ	<0.6 mΩ
ESR[2] (AC, 1 kHz)	<0.55 mΩ	<0.45 mΩ
Leakage Current IL[4]	<3.0 mA	<5.0 mA
Self-discharge Rate[5]	<20%	<20%
Constant Current (ΔT = 15°C)[6]	52 A	65 A
Max Current I_{Max}[7]	0.63 kA	0.99 kA
Short Current I_S[8]	4.3 kA	5.0 kA
Stored Energy E[9]	0.75 Wh	1.4 Wh
Energy Density E_d[10]	5.4 Wh/kg	7.0 Wh/kg
Usable Power Density P_d[11]	11.1 kW/kg	9.1 kW/kg
Matched Impedance Power Density P_{dMax}[12], 10 Hz ESR	23.1 kW/kg	19.0 kW/kg
Matched Impedance Power Density P_{dMax}[12], 1 kHz ESR	29.4 kW/kg	25.4 kW/kg

THERMAL CHARACTERISTICS		
Type	**C46W-3R0-0600**	**C46W-3R0-1100**
Working Temperature	-40 ~ 65°C	-40 ~ 65°C
Storage Temperature[13]	-40 ~ 70°C	-40 ~ 55°C
Thermal Resistance R_{Th}[14]	8.0 K/W	5.85 K/W
Thermal Capacitance C_{Th}[15]	155 J/K	240 J/K

LIFETIME CHARACTERISTICS		
Type	**C46W-3R0-0600**	**C46W-3R0-1100**
DC Life at High Temperature[16]	1500 hours	1500 hours
DC Life at RT[17]	10 years	10 years
Cycle Life[18]	Multimillion cycles	Multimillion cycles
Shelf Life[19]	4 years	4 years

SAFETY & ENVIRONMENTAL SPECIFICATIONS		
Type	**C46W-3R0-0600**	**C46W-3R0-1100**
Safety	RoHS, REACH and UL810	RoHS, REACH and UL810A
Vibration	IEC 60068-2-64 (table A.5/A.6)	IEC 60068-2-64 (table A.5/A.6)
Shock	IEC 60068-2-27, 100g 6ms	IEC 60068-2-27, 100g 6ms

All Rights Reserved

PHYSICAL PARAMETERS

Type		C46W-3R0-0600	C46W-3R0-1100
Mass M		139 g	197 g
Terminals		Weldable[20]	Weldable[20]
Dimensions[21]	Height L	67.4 mm	98.7 mm
	Diameter	46 mm	46 mm

NOTES:

1. Surge voltage V_S: Absolute maximum voltage, non-repetitive. The duration must not exceed 1 second.
2. Capacitance C: The test current is 0.075 A/F, if the calculated current is >100A, then apply 100A.



3. Capacitance tolerance: Typical tolerance is +10% ~ +30%.
4. Leakage current measurement procedure: 1) Charge the capacitor to the V_R with a constant current (0.075 A/F, if the calculated current is >100A, then apply 100A). 2) Hold the voltage at V_R for 72h. 3) The current to maintain V_R after 72 h is the leakage current.
5. Self-discharge rate measurement procedure: 1) Charge the capacitor to V_R with a constant current (0.075 A/F, if the calculated current >100A, then apply 100A). 2) Hold the voltage at V_R for 8h. 3) Floating for 72h. 4) Measure the voltage after 72 h.
6. Max constant working current: $I_{MCC} = \sqrt{\Delta T/(ESR * R_{Th})}$
7. Max current: $I_{Max} = 0.5C * V_R/(\Delta t + ESR * C)$, discharge from V_R to $V_R/2$ in 1 second.
8. Short current: $I_S = V_R/ESR$
9. Stored energy: $E = 0.5C * V^2/3600$
10. Energy density: $E_d = E/M$
11. Usable power density: $P_d = (0.12V_R^2/ESR)/M$
12. Matched impedance power density: $P_{dMax} = (0.25V_R^2/ESR)/M$
13. Storage temperature: Storage in discharge state at RT.
14. Thermal resistance: $R_{Th} = \Delta T/P$, where P = ESR * I^2
15. Thermal capacitance: For the whole capacitor
16. DC life at high temperature: Hold the capacitor charged at rated voltage at 65°C for 1500h. The capacitance shall be >80% of the rated value, the ESR shall be <200% of the rated value.
17. DC life at RT: Hold the capacitor charged at rated voltage at room temperature RT, the capacitance shall be >80% of the rated value, the ESR shall be <200% of the rated value.
18. Cycle life: The number of cycles depends on the charging and discharging characteristics.
19. Shelf life: Discharged and no load applied at RT.
20. The welding depth should be larger than 0.8 mm
21. Dimensions:

Standard markings:
+ Name of manufacturer, part number, serial number
+ Rated voltage and capacitance, negative and positive terminals, warning marking
+ Stored energy in watt-hours

Mounting recommendations:
+ Mounting without applying undue mechanical stress on the terminals
+ Provide adequate spacing in between cells to secure required insulation strength
+ Provide clearance around the safety vent and do not position anything above the safety vent that may be damaged in an event of vent rupture

The contents of this document are subject to change without notice. SECH accepts no liability for the accuracy or credibility of the values and information contained in this document.

All Rights Reserved